

## SPARTUS® 15000 roller rotator

Product code:

SP021-00-015



**\*the price does not include shipping costs**

**The time of order fulfillment: 6-7 weeks.**

### Product description

SPARTUS® roller rotators ensure smooth rotation of long elements. The solutions used guarantee no jerks and jumps, regardless of the weight of the element. The devices are equipped with gear covers, which additionally protect against welding waste and dust.

Benefits:

- geared motors with high torque
- rollers covered with polyurethane with a hardness of 92°ShA
- roller spacing adjustment by means of a trapezoidal screw

### ► MADE IN EU

### Technical parameters

Load capacity	15000kg
Linear speed	120-1200mm/min
Workpiece diameter	800-4000mm
Roller diameter	200mm
Input	~3× 400V ± 10% 50 / 60 Hz

PRODUCT CATEGORIES: [MACHINES](#), [WELDING ROTATORS](#), [POSITIONERS AND ROTATORS](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.