

SPARTUS® 2000 welding positioner

Product code:

SP020-02-000



***the price does not include shipping costs**

The time of order fulfillment: 6-7 weeks.

Product description

Welding positioners SPARTUS® with a load capacity from 300 kg are equipped with motors with electromagnetic brakes, which ensure work safety. Additionally, forced cooling used in the rotation motors guarantees failure-free operation for many years. The integrated control system ensures smooth adjustment of the rotational speed and the direction of rotation as well as the gradual, automatic adjustment of the disc tilt angle. It is equipped with a brush system, it is possible to connect the mass of the welding machine directly to the body of the positioner.

Advantages:

smooth regulation of rotation speed and selection of the direction of rotation

automatic, stepless adjustment of the disc tilt angle

electromagnetic brakes

rotary engine with cooling

reading the current speed

emergency stop – safety button on the control panel

current load in the 60% cycle 250A.

► MADE IN EU

Technical parameters

Load capacity	2000kg
Plate diameter	900/1100mm*
Rotation speed	0.12-1.2/0.5-5 r/min
Manual table tilt	90°/130°
Input	~3× 400V ± 10% 50 / 60 Hz
Weight	560kg

PRODUCT CATEGORIES: [MACHINES](#), [WELDING POSITIONERS](#), [POSITIONERS AND ROTATORS](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.