

SPARTUS® 300 welding positioner



Product code:

SP020-00-300

***the price does not include shipping costs**
The time of order to 6 weeks.

Product description

Welding positioners SPARTUS® with a load capacity to 300 kg are equipped with motors with electromagnetic brakes, which ensure work safety. Additionally, forced cooling used in the rotation motors guarantees failure-free operation for many years. The integrated control system ensures smooth adjustment of the rotational speed and the direction of rotation as well as the stepless, automatic adjustment of the disc tilt angle. It is equipped with a brush system, it is possible to connect the mass of the welding machine directly to the body of the positioner.

Advantages:

- smooth regulation of rotation speed and selection of the direction of rotation
- automatic, stepless adjustment of the disc tilt angle
- electromagnetic brakes
- rotary engine with cooling
- reading the current speed
- emergency stop - safety button on the control pendant
- current load in the 60% cycle 250A.

► MADE IN EU

Technical parameters

Load capacity	300kg
Plate diameter	600/800mm*
Rotation speed	0.12-1.2/0.5-5 r/min
Manual table tilt	90°/130°
Input	~3× 400V ± 10% 50 / 60 Hz
Weight	220kg

PRODUCT CATEGORIES: [MACHINES](#), [WELDING POSITIONERS](#), [POSITIONERS AND ROTATORS](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.