

SPARTUS® 3000 roller rotator

Product code:

SP021-00-003



***the price does not include shipping costs**

The time of order fulfillment: 3 weeks.

Product description

Easy to use and high mobility are the undoubted advantages of SPARTUS® roller rotators. They are dedicated to rotating pipes and cylinder-shaped elements. The use of rotators significantly improves the precision of machining, which affects the high quality of welds, while reducing the working time.

Benefits:

- inverter-based control
- three-phase motor
- comfortable grip
- rollers covered with polyurethane with a hardness of 92°ShA
- foot switch to start and stop rotation

► MADE IN EU

Technical parameters

Load capacity	3000kg (1500/section)
Linear speed	120-1200mm/min
Workpiece diameter	30-2500mm
Roller diameter	200mm
Input	~3× 400V ± 10% 50 / 60 Hz

PRODUCT CATEGORIES: [MACHINES](#), [WELDING ROTATORS](#), [POSITIONERS AND ROTATORS](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.