

SPARTUS® 5000 welding positioner



Product code:

SP020-05-000

***the price does not include shipping costs**

The time of order fulfillment: 6-8 weeks.

Product description

The SPARTUS® 5000 welding positioner is ideally suited to work with very heavy components, where manual operation could be dangerous and require a lot of time. The device is controlled by buttons on the manual control panel, and the rotation is started by a foot switch. It is equipped with a brush system, it is possible to connect the mass of the welding machine directly to the body of the positioner.

Advantages:

smooth regulation of rotation speed and selection of the direction of rotation

automatic, stepless adjustment of the disc tilt angle

reading the current speed

emergency stop – safety button on the control panel

current load in the 60% cycle 300A.

► MADE IN EU

Technical parameters

Load capacity	5000kg
Plate diameter	1200 mm
Rotation speed	0.06-0.6 / 0.1-1 rpm
Manual table tilt	90°/130°
Input	~3× 400V ± 10% 50 / 60 Hz
Weight	1200kg

PRODUCT CATEGORIES: [MACHINES](#), [WELDING POSITIONERS](#), [POSITIONERS AND ROTATORS](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.