

SPARTUS® EasyARC 250P



Product code:

EASYARC250P-PAK

Package equipped: • device SPARTUS® EasyARC 250P, • electrode holder, • work clamp, • user's manual

Product description

EasyARC 250P – EFFICIENT AND INTUITIVE MMA WELDER WITH PULSE

SPARTUS® EasyARC 250P is inverter welder that utilizes advanced IGBT technology. It is ideal for a wide range of welding applications, both MMA and TIG Lift, and is powered by a three-phase 400V supply.

HIGH EFFICIENCY



With current adjustment up to 250A, EasyARC 250P ensures high work efficiency. The device allows welding with electrodes up to 5mm in diameter and materials up to 6.2mm thick.

MMA PULSE WELDING

SPARTUS® EasyARC 250P in MMA Pulse mode provides more precise control over the welding process. Welders can set parameters such as pulse frequency and base current, which allows for precise adaptation of the device to specific conditions and materials. Pulse welding helps reduce thermal distortion, which is crucial when welding delicate materials or where minimizing deformation is key. The pulse function also reduces the risk of excessive metal spatter, thereby achieving cleaner and higher quality welds.

INNOVATIVE “SYN” FUNCTION

SPARTUS® EasyARC 250P features an innovative “SYN” function, which automatically adjusts the amperage and suggests the appropriate electrode diameter after the material thickness is entered. This function greatly simplifies and speeds up the preparation process.

ADDITIONAL SUPPORT FUNCTIONS

EasyARC 250P is equipped with supportive features such as Arc Force, Hot Start and VRD, which enhance user comfort and work efficiency by ensuring arc stability and easy arc initiation.

The modern solutions included in SPARTUS® EasyARC 250P make it an essential tool for those looking for reliability and high-quality welding in various working conditions. It is the perfect solution for workshops, production, and repair works where precision and power are required.

Technical parameters

Input

~3× 400V ± 10% 50 / 60 Hz

Welding current MMA [A]	10 - 250
Duty cycle MMA [%]	30
No-load voltage [V]	75
Additional features	pulse, Arc Force, Hot Start, VRD
Current consumption [A]	16
Power factor (cosφ)	0,81
Efficiency η [%]	86,7
Insulation class	H
Protection class	IP21S
Weight [kg]	11
Dimensions [mm]	500 x 220 x 310
Standards	CE , EN 60974-1 , EN 60974-10

PRODUCT CATEGORIES: [MACHINES](#), [MMA](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.