

SPARTUS® ProCUT 45PFC



SPARTUS® ProCUT 45PFC

Product code:

PROCUT45PFC-PAK-45H-6



Package equipped: • SPARTUS® ProCUT 45PFC • **Plasma torch SPARTUS® 45H 6m** • **With toolbox (free consumables kit)** • Built-in air filter with the pressure control • 3m work clamp • Gas hose • User's manual

* used with retaining cap – 6 holes (60389)

SPARTUS® ProCUT 45PFC



Product code:

PROCUT45PFC-PAK-SP45MY-7.5

Status:

News

Package equipped: • Device SPARTUS® ProCUT 45PFC • **Plasma torch SPARTUS® SP45MY 7.5m** • **With toolbox (free consumables kit)** • Built-in air filter with the pressure control • 3m work clamp • Gas hose • User's manual

SPARTUS® ProCUT 45PFC



Product code:

PROCUT45PFC-PAK-SP45HY-7.5

Status:

News

Package equipped: • Device SPARTUS® ProCUT 45PFC • **Plasma torch SPARTUS® 45H 6m** • **With toolbox (free consumables kit)** • Built-in air filter with the pressure control • 3m work clamp • Gas hose • User's manual

Product description

MODERN AND LIGHT PLASMA CUTTER

SPARTUS® ProCUT 45PFC is an inverter plasma cutter with integrated CNC control socket. Designed for cutting metals and other electrically conductive materials. It is powered with one-phase 230V source power.

Through the use of modern technology, we have obtained excellent source with maximum cutting current 40A. The maximum thickness of cut material is 25mm.

Built-in system of contactless pilot arc ignition without HF – provides excellent quality of cutting edge and longer life of consumables.

The easy-to-use panel with an LCD display allows for smooth adjustment of the cutting current and setting the appropriate pressure. In addition, the cutter is equipped with a 2T / 4T mode selector switch.

SPARTUS® ProCUT 45PFC is professional plasma cutter that will find application in manufacturing sectors, industry and as source of CNC plasma tables.

Technical parameters

Input	~1× 230V ± 10% 50 / 60 Hz
Cutting current [A]	20 - 40

Max. cutting thickness [mm]	25
Duty cycle [%]	60
Output working voltage [V]	18
Recomended work pressure [bar]	5
Air demand [l/min]	150
Additional features	2T/4T control , Post-gas
Contactless pilot arc ignition	without HF
Current consumption [A]	19.7
Power factor (cosφ)	0,7
Insulation class	H
Protection class	IP21S
Weight [kg]	14
Dimensions [mm]	600x 215 x 405

Other informations

PRODUCT CATEGORIES: [MACHINES](#), [PLASMA](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.