

# T220 exhaust fans



Product code:	SP030-99-T220
Status:	News

#### Order fulfillment time - 2 weeks

## **Product description**

### SPARTUS® exhaust fans

SPARTUS® exhaust fans are designed to work with extraction devices and systems that remove contaminated or clean air. Their aluminum impellers placed in metal enclosures ensure high flow efficiency and a spark-free design. SPARTUS® fans are intended for transporting non-explosive and chemically non-aggressive gases at temperatures up to 40°C. These devices excel at removing smoke or dust, especially in universal localized extraction systems, with retractable exhaust duct mechanisms or slotted duct extracts.

## Technical parameters

Ventilator	T220
Inlet diameter	200mm
Outlet diameter	200mm
Flow	3000m³/h
Noise level	80dB(A)
Power	2,2kW
Rotation speed	2800 obr/min
Protection class	IP54
Input	~3× 400V ± 10% 50 / 60 Hz
Weight	50kg

PRODUCT CATEGORIES: MACHINES, FANS, FILTER VENTILATION SYSTEMS

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.