

Thermo-crayons SPARTUS® 65°C

Product code: SP125-00-065

Quantity in package: 5 szt.

Product description

SPARTUS® thermo-crayons allow you to precisely determine temperature of treated metal. They are characterized by easy usage and wide range of available temperatures (from 45 ° C to 1200 ° C). Simply apply thermo-crayon on metal before heat treatment. After reaching specific temperature thermo-crayon will obtain liquid form. Thermo-crayons do not contain sulfur and lead.

Characteristics:

- Without sulfur and lead
- Easy-to-use
- Wide range of temperatures

Technical parameters

Temperature [°C] 65

Temperature [°F] 149

PRODUCT CATEGORIES: [THERMO-CRAYONS](#), [ACCESSORIES](#), [CHEMICAL](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.