

TIG 150R torch with SP9-90R rotary head, 4m, ProFLEX series, 1B, U package, SK35, 30cm hose.

Rec6



**Product code:**

SPP150RA-4-mSRP1B-U-1BEZ

## Product description

### SPARTUS® PROFLEX TIG 150R TORCH

SPARTUS® ProFLEX TIG torches manufactured in Poland are characterized by high quality of components used and solid workmanship. A wide selection of torch bodies, handles, microswitches and cable packages allows you to meet the expectations of even the most demanding welders.

#### CABLES





In the production of SPARTUS® ProFLEX torches, a professional cotton braided hose, made in the USA, was used. The high-density outer braid provides the highest level of flexibility, both at high and low temperatures.

#### CABLE PACKAGES

In SPARTUS® ProFLEX holders, 3 types of cable covers can be used. The „T” and „U” packages are manufactured in a textile-polyester cover, while the „X” package is made in a textile-rubber cover. The „U” and „X” packages also have a one-meter section of leather behind the handle.



textile-polyester cable package cover



textile-rubber cable package cover

#### TOOLBOX

SPARTUS® ProFLEX torches are equipped with a handy box containing consumables (toolbox).

#### ROTATING TORCH HEADS

Rotating SPARTUS® torch heads are an excellent solution for work carried out in hard-to-reach places. The body of the burner, thanks to its construction, allows the head to be rotated 360°. This solution increases the comfort and efficiency of work. In addition, the rotating torch head system allows you to quickly replace the head, depending on your needs. In the SP150R holders, heads of standard SP9/20 or SP17/18/26 can be used interchangeably.

#### WIDE CHOICE OF CONNECTIONS

Thanks to the wide range of connections, SPARTUS® ProFLEX torches can be used with many market-leading welding devices.

## POLISH PRODUCT

Torches SPARTUS® ProFLEX brand are made in Poland

*The picture of the torch presented in the article is illustrative and depends on the selected torch options.*

### Technical parameters

Rating	125A DC 100A AC
Electrode diameter [mm]	0.5, 1.0, 1.6, 2.0, 2.4
Gas flow rate [L/min]	7 - 15
Duty cycle [%]	80
Series	Pro
Cooling	gaz
Torch body	9 [małe części], wymienne obrotowe główki palnika
Torch body	standard
Lenght [m]	4
Handle	okrągła
Microswitch	pojedynczy
Package	pakiet w osłonie tekstylno-poliestrowej + 1m skóry

**Connections**

SK35

PRODUCT CATEGORIES: GAS COOLED

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.