

TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit to ESAB®



Product code:

SPP225FA-4-mSRP1B-U-2ESB

Product description

SPARTUS® PROFLEX TIG 225F TORCH

SPARTUS® ProFLEX TIG torches manufactured in Poland are characterized by high quality of components used and solid workmanship. A wide selection of torch bodies, handles, microswitches and cable packages allows you to meet the expectations of even the most demanding welders.

CABLES





In the production of SPARTUS® ProFLEX torches, a professional cotton braided hose, made in the USA, was used. The high-density outer braid provides the highest level of flexibility, both at high and low temperatures.

CABLE PACKAGES

In SPARTUS® ProFLEX holders, 3 types of cable covers can be used. The „T” and „U” packages are manufactured in a textile-polyester cover, while the „X” package is made in a textile-rubber cover. The „U” and „X” packages also have a one-meter section of leather behind the handle.



textile-polyester cable package cover



textile-rubber cable package cover

TOOLBOX

SPARTUS® ProFLEX torches are equipped with a handy box containing consumables (toolbox).

REPLACEABLE TORCH HEADS

Replaceable SPARTUS® torch heads are an innovative solution that allows for instant replacement of the head, depending on the needs – size of the head, angle of inclination. In the SP155F holders, heads of the standard SP24/24W, SP9/20 or SP17/18/26 can be used interchangeably.

WIDE CHOICE OF CONNECTIONS

Thanks to the wide range of connections, SPARTUS® ProFLEX torches can be used with many market-leading welding devices.

POLISH PRODUCT

Torches SPARTUS® ProFLEX brand are made in Poland

The picture of the torch presented in the article is illustrative and depends on the selected torch options.

Technical parameters

| | |
|-----------------------------|-------------------------|
| Rating | 125A DC 100A AC |
| Electrode diameter [mm] | 0.5, 1.0, 1.6, 2.0, 2.4 |
| Gas flow rate [L/min] | 7 - 20 |
| Liquid cooling flow [L/min] | 1.0 - 1.5 |
| Duty cycle [%] | 100 [super flex] |
| Series | Pro |
| Cooling | ciecz |
| Torch body | 225F [małe części] |
| Torch body | flex |
| Length [m] | 4 |

| | |
|--------------------|--|
| Handle | mała |
| Microswitch | pojedynczy |
| Package | pakiet w osłonie tekstylno-poliestrowej + 1m skóry |
| Connections | 2ESB |

PRODUCT CATEGORIES: [TIG TORCHES](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.