

# TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit to

# MAGNUM®



**Product code:** 

SPP225FA-4-mSRP1B-U-1MAG

# **Product description**

SPARTUS® PROFLEX TIG 225F TORCH

SPARTUS® ProFLEX TIG torches manufactured in Poland are characterized by high quality of components used and solid workmanship. A wide selection of torch bodies, handles, microswitches and cable packages allows you to meet the expectations of even the most demanding welders.









In the production of SPARTUS® ProFLEX torches, a professional cotton braided hose, made in the USA, was used. The high-density outer braid provides the highest level of flexibility, both at high and low temperatures.

#### **CABLE PACKAGES**

In SPARTUS® ProFLEX holders, 3 types of cable covers can be used. The "T" and "U" packages are manufactured in a textile-polyester cover, while the "X" package is made in a textile-rubber cover. The "U" and "X" packages also have a one-meter section of leather behind the handle.



textile-polyester cable package cover



textile-rubber cable package cover

#### **TOOLBOX**

SPARTUS® ProFLEX torches are equipped with a handy box containing consumables (toolbox).

#### REPLACEABLE TORCH HEADS

Replaceable SPARTUS® torch heads are an innovative solution that allows for instant replacement of the head, depending on the needs – size of the head, angle of inclination. In the SP155F holders, heads of the standard SP24/24W, SP9/20 or SP17/18/26 can be used interchangeably.

#### WIDE CHOICE OF CONNECTIONS

Thanks to the wide range of connections, SPARTUS® ProFLEX torches can be used with many market-leading welding devices.

# **POLISH PRODUCT**

Torches SPARTUS® ProFLEX brand are made in Poland

The picture of the torch presented in the article is illustrative and depends on the selected torch options.

# Technical parameters

Electrode diameter [mm]0.5, 1.0, 1.6, 2.0, 2.4Gas flow rate [L/min]7 - 20Liquid cooling floow [L/min]1.0 - 1.5Duty cycle [%]100 [super flex]SeriesProCoolingcieczTorch body225F [małe części]Torch bodyflexLenght [m]4	Rating	125A DC 100A AC
Liquid cooling floow [L/min]1.0 - 1.5Duty cycle [%]100 [super flex]SeriesProCoolingcieczTorch body225F [małe części]Torch bodyflex	Electrode diameter [mm]	0.5, 1.0, 1.6, 2.0, 2.4
Duty cycle [%]100 [super flex]SeriesProCoolingcieczTorch body225F [małe części]Torch bodyflex	Gas flow rate [L/min]	7 - 20
SeriesProCoolingcieczTorch body225F [małe części]Torch bodyflex	Liquid cooling floow [L/min]	1.0 - 1.5
CoolingcieczTorch body225F [małe części]Torch bodyflex	Duty cycle [%]	100 [super flex]
Torch body 225F [małe części] Torch body flex	Series	Pro
Torch body flex	Cooling	ciecz
	Torch body	225F [małe części]
Lenght [m] 4	Torch body	flex
	Lenght [m]	4



Handle	mała
Microswitch	pojedynczy
Package	pakiet w osłonie tekstylno-poliestrowej + 1m skóry
Connections	1MAG

### PRODUCT CATEGORIES: TIG TORCHES

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, LTEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.