

Torch body SP17F flex L=73mm (gas)

Product code:

SP17F

Technical parameters

| | |
|-------------------------------|--|
| Brand | SPARTUS Master, SPARTUS Pro |
| Application | 17 / 18 / 26 / 170F / 26MP / 250F / 1726R / 1726 / 1726P |
| Torch body type | flex |
| Cooling | gas |
| Load DC [A] | 150 |
| Load AC [A] | 115 |
| Electrode diameter range [mm] | 0.5 - 3.2 |
| Gas flow rate [L/min] | 7 - 15 |

PRODUCT CATEGORIES: [CONSUMABLES](#), [17 / 18 / 26 / 170F / 26MP / 250F / 1726R / 1726 / 1726P](#), [TORCHES BODY](#), [TIG](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.