

Torch body SP26S short L=71mm (gas)



Product code:	SP26S
Status:	News

Technical parameters

Brand	SPARTUS Master, SPARTUS Pro
Application	17 / 18 / 26 / 170F / 26MP / 250F / 1726R / 1726 / 1726P
Torch body type	standard
Cooling	gas
Load DC [A]	200
Load AC [A]	150
Electrode diameter range [mm]	0.5 - 4.0
Gas flow rate [L/min]	7 - 20

PRODUCT CATEGORIES: [CONSUMABLES](#), [17 / 18 / 26 / 170F / 26MP / 250F / 1726R / 1726 / 1726P](#), [TORCHES BODY](#), [TIG](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.