

Torch body SPARTUS Master/Pro 9FXXL



Product code:	SP9FXXL
Status:	News

Technical parameters

Brand	SPARTUS Master, SPARTUS Pro
Application	9 / 20 / 20HD / 22 / 25 / 9-90R / 9-70 / 9-90 / 9-P
Torch body type	flex
Cooling	gas
Load DC [A]	125
Load AC [A]	100
Electrode diameter range [mm]	0.5 - 2.4
Gas flow rate [L/min]	7 - 15

PRODUCT CATEGORIES: CONSUMABLES, 9 / 20 / 20HD / 22 / 25 / HEAD: 9-90R / 9-70 / 9-90 / 9-P, TORCHES BODY, TIG

 $NW \otimes is$ independent subject and not connected to $ABITIG \otimes$, $AMPHENOL \otimes$, $ASPA \otimes$, $BESTER \otimes$, $BINZEL \otimes$, $CEA \otimes$, $CEBORA \otimes$, $ESAB \otimes$, $EWM \otimes$, $FALTIG \otimes$, $FRO \otimes$, $FRONIUS \otimes$, $HARRIS \otimes$, $HYPERTHERM \otimes$, $KJELLBERG \otimes$, $LTEC \otimes$, $LINCOLN \otimes$, $MAGNUM \otimes$, $OTC \otimes$, $SAF \otimes$, $SHERMAN \otimes$, $TELWIN \otimes$, $THERMAL DYNAMICS \otimes$, $TRAFIMET \otimes$, $TUCHEL \otimes$.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.