

Torch body SPE20 L=57mm (liquid)

Product code: SPE20

Technical parameters

| | |
|-------------------------------|---|
| Brand | SPARTUS Easy |
| Application | 9 / 20 / 20HD / 22 / 25 / 9-90R / 9-70 / 9-90 / 9-P |
| Torch body type | standard |
| Cooling | liquid |
| Load DC [A] | 250 |
| Load AC [A] | 200 |
| Electrode diameter range [mm] | 0.5 - 3.2 |
| Gas flow rate [L/min] | 7 - 20 |
| Liquid cooling flow [L/min] | 1.0 - 1.5 |

PRODUCT CATEGORIES: [CONSUMABLES](#), [9 / 20 / 20HD / 22 / 25 /](#) [HEAD: 9-90R / 9-70 / 9-90 / 9-P](#), [TORCHES BODY](#), [TIG](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.