

Torch body SPE24W L=66mm (liquid)

Product code: SPE24W

Technical parameters

Brand	SPARTUS Easy
Application	24 / 24W / 24-70 / 24-90
Torch body type	standard
Cooling	liquid
Load DC [A]	180
Load AC [A]	100
Electrode diameter range [mm]	0.5 - 2.4
Gas flow rate [L/min]	7 - 20
Liquid cooling flow [L/min]	1.0 - 1.5

PRODUCT CATEGORIES: [24 / 24W / 24-70 / 24-90](#), [CONSUMABLES](#), [TORCHES BODY](#), [TIG](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.