

Torch body SPE26FV flex with valve L=88mm (gas)

Product code: SPE26FV

Technical parameters

Brand	SPARTUS Easy
Application	17 / 18 / 26 / 170F / 26MP / 250F / 1726R / 1726 / 1726P
Torch body type	flex, with valve
Cooling	gas
Load DC [A]	200
Load AC [A]	150
Electrode diameter range [mm]	0.5 - 4.0
Gas flow rate [L/min]	7 - 20

PRODUCT CATEGORIES: [CONSUMABLES](#), [17 / 18 / 26 / 170F / 26MP / 250F / 1726R / 1726 / 1726P](#), [TORCHES BODY](#), [TIG](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.