

Torch body SPE9FXL flex L=108mm (gas)

Product code: SPE9FXL

Technical parameters

Brand	SPARTUS Easy
Application	9 / 20 / 20HD / 22 / 25 / 9-90R / 9-70 / 9-90 / 9-P
Torch body type	flex, extended
Lenght [mm]	105
Cooling	gas
Load DC [A]	125
Load AC [A]	100
Electrode diameter range [mm]	0.5 - 2.4
Gas flow rate [L/min]	7 - 15

PRODUCT CATEGORIES: [CONSUMABLES](#), [9 / 20 / 20HD / 22 / 25 /](#) [HEAD: 9-90R / 9-70 / 9-90 / 9-P](#), [TORCHES BODY](#), [TIG](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.