

This exploded view diagram illustrates the assembly of a surgical instrument. The components are numbered as follows:

- 1**: Main handle assembly with a trigger and control buttons.
- 1a**: A connector or coupling component.
- 2**: A long, angled shaft or arm.
- 2a**: A connector or coupling component for the shaft.
- 3**: A small component, possibly a switch or sensor, located near the trigger.
- 4**: A long, thin component, possibly a probe or needle.
- 5**: A component at the end of the long thin assembly.
- 6**: A component that fits onto the end of the long thin assembly.
- 7**: A small component, possibly a seal or O-ring.
- 8**: A threaded component, possibly a nut or washer.
- 9**: A component that fits onto the threaded part.
- 10**: A component that fits onto the end of the main handle assembly.
- 11**: A component that fits onto the end of the main handle assembly.
- 12**: A component that fits onto the end of the main handle assembly.
- 13**: A component that fits onto the end of the main handle assembly.
- 14**: A component that fits onto the end of the main handle assembly.
- 15**: A component that fits onto the end of the main handle assembly.
- 16**: A component that fits onto the end of the main handle assembly.
- 17**: A component that fits onto the end of the main handle assembly.
- 18**: A component that fits onto the end of the main handle assembly.
- 19**: A component that fits onto the end of the main handle assembly.
- 20**: A component that fits onto the end of the main handle assembly.
- 21**: A component that fits onto the end of the main handle assembly.
- 22**: A component that fits onto the end of the main handle assembly.
- 23**: A component that fits onto the end of the main handle assembly.
- 24**: A component that fits onto the end of the main handle assembly.

www.nweld.infoen | Page: 1 / 2

Lp.	Product code	[H]	[M]	Nr ref.	Product name	Net price
2a	NW01200	:	:		Hand torch head	
3	NW07301.20	■			Microswitch	
4	NW01400		■		Machine torch head	
5	NW03310		■		Machine handle	
6	NW60085	■	■		Front insulator	
7	NW06004	■	■		Diffusor	
8	NW52540	■	■		Electrode	
9	NW60020	■	■		Swirl ring	
10	NW51140S	:	:		Tip fi 1.1 Long Life	
	NW51141S	■	■		Tip fi 1.35 Long Life	
	NW51142S	:	:		Tip fi 1.6 Long Life	
	NW51144.24	■			Gouging tip fi 2.4	
11	NW60328	■			Retaining cap	
12	NW51910	■			Spacer spring	
13	NW60370	■			Double pointed spacer	
14	NW60371	■			Crown spacer	
15	NW60373	■			Gouging spacer	
16	NW60348	■	■		Contact retaining cap	
	NW60348V	■	■		Contact retaining cap Max Life	
17	NW51953	■			Gouging spacer	
18	NW51952	■			Spring holder protection nut	
19	NW51911	■			Spacer spring	
20	NW51950	■			Spacer for contact cutting hand	
21	NW51959	■	■		Locking nut	
22	NW51951		■		Shield cap, machine	
23	NW60369	■	■		Extractor for swirl ring	
24	NW60368	■	■		Wrench for electrode	
	NW04241	■			Cable, 6m 1/8" – Hand torch	
	NW04321		■		Cable, 6m 1/8" – Machine torch	

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.