



TECHNICAL PARAMETERS

Input [V]	Welding current [A]	Duty cycle [%]	Pulse Amps [A]	AC frequency [Hz]	AC balance [%]	Weight [kg]	Dimensions [mm]
230	TIG 10 – 200 AC / 10 – 170 DC MMA 10 – 170 AC/DC	TIG AC 35[200A] / DC 40[170A] MMA AC/DC 40[170A]	AC 10 - 200 DC 10 - 170	60	10 – 99	8,7	450 × 135 × 230

Additional features: 2T/4T, pulse, output remote control, HOT START, ARC FORCE, POST GAS, PRE GAS

DESCRIPTION

SPARTUS® EasyTIG 210P AC/DC is a modern digitally controlled inverter welding machine, constructed on the basis of IGBTs. Allows welding TIG AC/DC and MMA AC/DC modes. It is powered with single-phase 230V source power. Versatile unit for a wide range of applications. It has a simple-to-use digital control panel that provides instant access to the welding machine's functions. Allows to weld steel, stainless steel (TIG DC pulse welding – allows to weld thin elements). TIG AC welding function allows to weld aluminium and its alloys. Welder is ready to work with TIG torches equipped with remote control (in the handle).

SPARTUS® Easy TIG 210P AC / DC impresses small dimensions and lightweight of just 8,7kg. It is ideal for maintenance, assembly, as well as production works.

Examples of use: portable repair, workshop, maintenance, constructions.

ADDITIONAL OPTIONS

Wire foot pedal for TIG welding machines, allows remote control of current during welding. The value of the current depends on the pressure of the operator's foot. It is a perfect solution for precise TIG welding on a stationary welding station. Cable lengths available: 5m, 10m, 15m, 20m.



STANDARD:

3m work clamp
gas hose
user's manual

PACKAGE 4m:

TIG torch SPE 26 4B X 4m
TIG equipment
electrode holder
gas hose
3m work clamp
user's manual

PACKAGE 8m:

TIG torch SPE 26 4B X 8m
TIG equipment
electrode holder
gas hose
5m work clamp
user's manual

