
# SPARTUS<sup>®</sup> EasyMIG 185



LIGHT AND PORTABLE MIG 3in1



# **Description** TECHNICAL PARAMETERS

	Input [V]	Welding current [A]	Duty cycel MIG [%]	Wire feeder	Welding wire spool [kg]/[mm]	Wire diameter [mm]	Weight [kg]	Dimensions [mm]
	230	мід 40 – 180 тід 10 – 180	35	wbudowany, 2 - rolkowy	≤ 5 / Ø200	0.6/0.8/1.0	15	535 × 230 × 410
		мма 10 – 180						

Additional features: 2T/4T, inductance, polarity change, DOWN SLOPE, ARC FORCE, VRD



**SPARTUS® EasyMIG 185** is a modern inverter, semi-automatic welding unit. It supports welding by means of a consumable electrode shielded by inert (MIG) or active (MAG) gases, welding with coated electrode (MMA) and tungsten inert gas (TIG Lift) welding with scratch ignition. The maximum welding current for all three techniques is 180A. The unit is powered from a single-phase 230V network. The user-friendly control panel allows for instant adjustment of welding parameters depending on the selected technique:

- MIG/MAG welding techniques stepless adjustment of welding voltage, wire feed rate and inductance
- MMA welding technique stepless adjustment of current intensity and Arc Force values (0 10)
- TIG Lift stepless adjustment of welding current intensity and down slope values (0 10)

# 🙆 WIRE FEEDER

Ultralight and portable EasyMIG welding unit. It is equipped with a two-roller welding wire feeder. In addition, thanks to a capability of polarity change, it supports gas-free self-shielding wire welding.



#### **SPARTUS®** EasyMIG 185

### PACKAGE EQUIPMENT:

MIG gun SPARTUS<sup>®</sup> SPE 150 3m electrode holder work camp gas hose user's manual





**Possibility of welding TIG torch with a microswitch** SPE17-4-mSRE1B-D-9SPA



www.spartus.info