



TECHNICAL PARAMETERS

Input [V]	Welding current [A]	Duty cycle MIG [%]	Wire feeder	Welding wire spool [kg]/[mm]	Wire diameter [mm]	Weight [kg]	Dimensions [mm]
230	MIG 40 - 200 TIG 20 - 160	60	built-in 2 - roll gear	≤ 5/Ø200	0.6/0.8/1.0	10	400 × 195× 270

Additional features: 2T/4T, inductance, polarity change, BURN BACK, voltage compensation

SPARTUS® EasyMIG 200 is a semi-automatic welding machine made in inverter technology. Allows welding in an inert and active gas shield (MIG/MAG), coated electrode (MMA) and TIG Lift with arc ignition. In addition, the device thanks to the ability to change the polarity of welding, enables welding with flux cored welding wire without gas.

Maximum welding current for MIG method is 200A, and for MMA and TIG Lift – 160A. The unit is powered from a single-phase network 230V.

The easy-to-use control panel allows for quick adjustment of welding parameters. EasyMIG 200 is characterized by a simple synergy in which only the wire diameter is determined for the selected gas. The device has functions supporting the welding process: 2T/4T, Burn Back, inductance adjustment, voltage compensation.



Light EasyMIG is equipped with a two-roll welding wire feeder, which ensures smooth and even feeding of the welding wire.



SPARTUS® EasyMIG 200



PACKAGE EQUIPMENT:

MIG gun SPARTUS® SPE 150 3m electrode holder work camp gas hose user's manual

