



# SPARTUS® ProMIG 525 DP

SYNERGIC MIG WITH DUAL PULSE  
DESIGNED FOR INDUSTRY



## SYNERGY PARAMETERS

Material	Wire Diameter (mm)	Shielding Gas
FE-metal Solid-cored	0,8 / 0,9 / 1,0 / 1,2 / 1,6	CO <sub>2</sub> / Ar+CO <sub>2</sub> 20%
FE-metal Flux-cored	0,9 / 1,0 / 1,2 / 1,6	CO <sub>2</sub>
SS-metal Solid-cored	0,9 / 1,0 / 1,2 / 1,6	Ar+O <sub>2</sub> 2%
Al-Mg Solid-cored	1,0	Ar
CuSi	1,0	Ar

## TECHNICAL PARAMETERS

Input [V]	Welding current [A]	Duty cycle [%]	Wire feeder	Welding wire spool [kg]/[mm]	Wire diameter [mm]	Weight [kg]	Dimensions [mm]
400	MIG 40 – 500 TIG 10 – 500 MMA 10 – 500	60	separate, 4-roll gear	≤ 15 / Ø200/300	0.6 / 0.8 / 1.0 / 1.2 / 1.6	101.5	1100 × 500 × 1460

**Additional Features:** 1P (Pulse), 2P (Dual Pulse), pre gaz, post gaz, 2T / 4T operating mode, Spool Gun, synergy, Hot Start, Arc Force.

## DESCRIPTION

**SPARTUS® ProMIG 525 DP** is high-end, modern inverter welding machine constructed on the basis of advanced PWM technology and professional IGBT transistors. It enables MIG / TIG DC and MMA welding with a current up to 500A. It is powered from three phase 400V source power. The device offers a wide range of possibilities for the above-mentioned methods of joining metals.

**ProMIG 525 DP** is equipped with a synergistic system for MIG / MAG welding with the possibility of selecting the following programs: for mill steel, stainless steel, aluminum welding; self-shielding wire welding and braze welding. It is possible to manually correct the parameters. In addition, the device has a number of functionalities supporting the welding process in the MIG methods: 1P (Pulse), 2P (Dual Pulse), JOB mode – save and call 100 different job records, 2T/4T / s4T / SPOT Trigger Control, Burn Back, Slow Feed, Pre Gas and Post Gas. Separate high-class four-roller feeder ensures stable wire feeding. An important advantage is also the possibility of welding with the Spool Gun.

Thanks to the solutions used, the **ProMIG 525 DP** also enables advanced welding with the TIG Lift method.

**ProMIG 525 DP** has functions supporting the welding process in TIG methods: 2T/4T Trigger Control, Down Slope.

The process of joining metals in MMA method is additionally supported by functions Arc Force and Hot Start.

Modern design, LCD function panel and the possibility of wireless control in combination with high-class components makes the **SPARTUS® ProMIG 525 DP** stand out on the market.

The professional device of the **SPARTUS® Pro** line is perfect suited to the production sector and industry.



**STANDARD:**

- Separated wire feeder 4R
- Cooler
- Driving set
- 3m mass cable with screw clamp
- User's manual

**PACKAGE:**

- Separated wire feeder 4R
- Cooler
- Driving set
- MIG gun SPARTUS® SPP 501
- 5m connection cable set
- 3m electrode holder
- 3m mass cable with screw clamp
- User's manual

