



TECHNICAL PARAMETERS

Input [V]	Cutting current [A]	Max. cutting thickness [mm]	Duty cycle [%]	Recomended work pressure [bar]	Weight [kg]	Dimensions [mm]
230	20 – 40	16	30	4.5	6.5	440 × 145 × 245

DESCRIPTION

SPARTUS® EasyCUT 40s is a small size inverter plasma cutter with adjustable cutting current in the range of 20-40 amps. Through the use of modern technology, we were able to get a light and compact device. The machine gives possibilities for cutting metals and other electrically conductive materials. The maximum thickness of cutting elements is 16mm.

Device has a simple-to-use functional panel that allows you to easily control the machine, even with gloves. The 2T / 4T mode switch allows you to work with the torch according to the user's preferences. Device's front panel is equipped with a SK socket and the plasma torch socket.

SPARTUS® EasyCUT 40s is equipped with a pressure reducer with air filter which is mounted on the back of the cover, in a place specially designed for that purpose (protection against damage eg. during the move).


Device has built-in system of contactless pilot arc ignition without HF – provides excellent quality of cutting edge and longer life of consumables.

SPARTUS® EasyCUT 40s in ready-to-work package includes a work clamp and a complete plasma torch – 4m SPARTUS® SP45H.

Examples of use: workshop, portable repair.



SPARTUS® EasyCUT 40s



PACKAGE EQUIPMENT:

plasma torch SPARTUS® 45H 4m
air filter with the pressure control
work clamp
user's manual

